

# 1MBC10-060, 1MBC10D-060, 1MBG10D-060

Molded IGBT

## 600V / 10A


## Molded Package

### ■ Features

- Small molded package
- Low power loss
- Soft switching with low switching surge and noise
- High reliability, high ruggedness (RBSOA, SCSOA etc.)
- Comprehensive line-up

### ■ Applications

- Inverter for Motor drive
- AC and DC Servo drive amplifier
- Uninterruptible power supply




### ■ Maximum ratings and characteristics

- Absolute maximum ratings (at  $T_c=25^\circ\text{C}$  unless otherwise specified)

#### 1MBC10-060 / IGBT


Item	Symbol	Rating	Unit
Collector-Emitter voltage	$V_{CES}$	600	V
Gate-Emitter voltage	$V_{GES}$	$\pm 20$	V
Collector current	DC	$T_c=25^\circ\text{C}$	$I_{C25}$ 20 A
		$T_c=100^\circ\text{C}$	$I_{C100}$ 10 A
	1ms	$T_c=25^\circ\text{C}$	$I_{cp}$ 80 A
Max. power dissipation (IGBT)	$P_C$	75	W
Operating temperature	$T_J$	+150	$^\circ\text{C}$
Storage temperature	$T_{stg}$	-40 to +150	$^\circ\text{C}$
Screw torque	-	40	Ncm

### ■ Equivalent Circuit Schematic



#### 1MBC10D-060, 1MBG10D-060 / IGBT+FWD

Item	Symbol	Rating	Unit
Collector-Emitter voltage	$V_{CES}$	600	V
Gate-Emitter voltage	$V_{GES}$	$\pm 20$	V
Collector current	DC	$T_c=25^\circ\text{C}$	$I_{C25}$ 20 A
		$T_c=100^\circ\text{C}$	$I_{C100}$ 10 A
	1ms	$T_c=25^\circ\text{C}$	$I_{cp}$ 80 A
Max. power dissipation (IGBT)	$P_C$	75	W
Max. power dissipation (FWD)	$P_C$	35	W
Operating temperature	$T_J$	+150	$^\circ\text{C}$
Storage temperature	$T_{stg}$	-40 to +150	$^\circ\text{C}$
Screw torque	-	40	Ncm



● Electrical characteristics (at Tj=25°C unless otherwise specified)

1MBC10-060 / IGBT

Item	Symbol	Characteristics			Conditions	Unit
		Min.	Typ.	Max.		
Zero gate voltage collector current	ICES	-	-	1.0	VGE=0V, VCE=600V	mA
Gate-Emitter leakage current	IGES	-	-	20	VCE=0V, VGE=±20V	μA
Gate-Emitter threshold voltage	VGE(th)	5.5	-	8.5	VCE=20V, IC=10mA	V
Collector-Emitter saturation voltage	VCE(sat)	-	-	3.0	VGE=15V, IC=10A	V
Input capacitance	Cies	-	700	-	VGE=0V	pF
Output capacitance	Coes	-	150	-	VCE=10V	
Reverse transfer capacitance	Cres	-	20	-	f=1MHz	
Turn-on time	ton	-	-	1.2	VCC=300V IC=10A	μs
	tr	-	-	0.6	VGE=±15V	
Turn-off time	toff	-	-	1.0	RG=220 ohm	μs
	tr	-	-	0.35	(Half Bridge)	

1MBC10D-060, 1MBG10D-060 / IGBT+FWD

Item	Symbol	Characteristics			Conditions	Unit
		Min.	Typ.	Max.		
Zero gate voltage collector current	ICES	-	-	1.0	VGE=0V, VCE=600V	mA
Gate-Emitter leakage current	IGES	-	-	20	VCE=0V, VGE=±20V	μA
Gate-Emitter threshold voltage	VGE(th)	5.5	-	8.5	VCE=20V, IC=10mA	V
Collector-Emitter saturation voltage	VCE(sat)	-	-	3.0	VGE=15V, IC=10A	V
Input capacitance	Cies	-	700	-	VGE=0V	pF
Output capacitance	Coes	-	150	-	VCE=10V	
Reverse transfer capacitance	Cres	-	20	-	f=1MHz	
Turn-on time	ton	-	-	1.2	VCC=300V IC=10A	μs
	tr	-	-	0.6	VGE=±15V	
Turn-off time	toff	-	-	1.0	RG=220 ohm	μs
	tr	-	-	0.35	(Half Bridge)	
FWD forward on voltage	VF	-	-	3.0	IF=10A, VGE=0V	V
Reverse recovery time	trr	-	-	0.3	IF=10A, VGE=-10V, di/dt=100A/μs	μs

● Thermal resistance characteristics

1MBC10-060 / IGBT

Item	Symbol	Characteristics			Conditions	Unit
		Min.	Typ.	Max.		
Thermal resistance	Rth(j-c)	-	-	1.66	IGBT	°C/W


1MBC10D-060, 1MBG10D-060 / IGBT+FWD

Item	Symbol	Characteristics			Conditions	Unit
		Min.	Typ.	Max.		
Thermal resistance	Rth(j-c)	-	-	1.66	IGBT	°C/W
	Rth(j-c)	-	-	3.57	FWD	°C/W

■ Outline drawings, mm


1MBC10-060, 1MBC10D-060

TO-220AB



1MBG10D-060

T pack-S (SMD type)




Characteristics

1MBC10-060, 1MBC10D-060, 1MBG10D-060


Collector current vs. Collector-Emitter voltage

T<sub>j</sub>=25°C




Collector current vs. Collector-Emitter voltage

T<sub>j</sub>=125°C




Collector-Emitter vs. Gate-Emitter voltage

T<sub>j</sub>=25°C




Collector-Emitter vs. Gate-Emitter voltage

T<sub>j</sub>=125°C




Switching time vs. Collector current

V<sub>CC</sub>=300V, R<sub>G</sub>=220 ohm, V<sub>GE</sub>=±15V, T<sub>j</sub>=25°C









Switching time vs. Collector current

V<sub>CC</sub>=300V, R<sub>G</sub>=220 ohm, V<sub>GE</sub>=±15V, T<sub>j</sub>=125°C



Characteristics


1MBC10-060, 1MBC10D-060, 1MBG10D-060



■ Characteristics


1MBC10-060, 1MBC10D-060, 1MBG10D-060

Transient thermal resistance




1MBC10D-060, 1MBG10D-060


Reverse recovery time vs. Forward current



Reverse recovery current vs. Forward current



Forward current vs. Forward voltage



Reverse recovery time characteristics vs. -di/dt

