

型名	社名	用途	最大定格 (Ta=25°C, *印はTc=25°C)					電気的特性 (Ta=25°C) [*印はtyp値]									
			V _{CEO}	V _{CE0}	I _{C(DC)}	P _c	P _{c*}	I _{CEO} (max) (μA)	V _{CE} (V)	(min)	h _{FE} (max)	V _{CE} (V)	I _{C/I_E} (A)	V _{CE(sat)} (max) (V)	V _{BE(sat)} (max) (V)	I _C (A)	I _B (A)
			(V)	(V)	(A)	(W)	(W)										
DTD113E*	ローム	INV/ D/ SW	50		0.5	.3/0.6				33		5	0.05	0.3		-0.05	
DTD113Z*	ローム	INV/ D/ SW	50		0.5	.3/0.6				56		5	0.05	0.3		-0.05	
DTD114E*	ローム	INV/ D/ SW	50		0.5	.3/0.6				56		5	0.05	0.3		-0.05	
DTD114T*	ローム	INV/ D/ SW	50	50	0.5	.3/0.6	0.5	30	100	600	5	0.05	0.3	0.05	0.0025		
DTD123E*	ローム	INV/ D/ SW	50		0.5	.3/0.6				39		5	0.05	0.3		-0.05	
DTD123T*	ローム	INV/ D/ SW	50	50	0.5	.3/0.6	0.5	30	100	600	5	0.05	0.3	0.05	0.0025		
DTD123Y*	ローム	INV/ D/ SW	50		0.5	.3/0.6				56		5	0.05	0.3		-0.05	
DTD133H*	ローム	INV/ D/ SW	50		0.5	.3/0.6				56		5	0.05	0.3		-0.05	
DTD143E*	ローム	INV/ D/ SW	50		0.5	.3/0.6				47		5	0.05	0.3		-0.05	
DTD143T*	ローム	INV/ D/ SW	50	50	0.5	.3/0.6	0.5	30	100	600	5	0.05	0.3	0.05	0.0025		
DTD163T*	ローム	INV/ D/ SW	50	50	0.5	.3/0.6	0.5	30	100	600	5	0.05	0.3	0.05	0.0025		
ET189	富士電機	HV HS PSW/PA/PD/SW-Reg	300		40		100	1000	300	100	5	20	2.2	2.5	20	1	
ET206	富士電機	HV HS PSW/PA/PD/SW-Reg	850	500	10		80	1000	850	15	5	1	1.5	1.2	4	0.8	
ET383	富士電機	HV HS PSW/PA/PD/SW-Reg	1000		5		80	1000	1000	10	5	2	1	1.5	2	0.4	
ET394	富士電機	HV HS PSW/PA/PD/SW-Reg	900	800	5		80	1000	900	10	5	2	1	1.5	2	0.4	
ET400	富士電機	HV HS PSW/PA/PD/SW-Reg	500	400	10		80	1000	500	10	5	5	1	1.5	5	1	
ET401	富士電機	HV HS PSW/PA/PD/SW-Reg	500	400	15		80	1000	500	10	5	6	1	1.5	6	1.2	
ET403	富士電機	HV HS PSW/PA/PD/SW-Reg	850	500	6		40	1000	850	15	5	0.5	0.5	1.2	2	0.4	
ET405	富士電機	HV HS PSW/PA/PD/SW-Reg	450	400	10		80	1000	450	10	5	4	1.2	1.5	4	0.8	
ET-102	富士電機	HV HS PSW/PA/PD/SW-Reg	600	450	100		770	1000	600	50	2	100	2	3	100	2	
ET-125	富士電機	HV HS PSW/PA/PD/SW-Reg	400	300	50		300	1000	400	150	5	50	2	2.5	50	1	
ET-127	富士電機	HV HS PSW/PA/PD/SW-Reg	600	450	100		770	1000	600	100	5	100	2	3	100	2	
ET-188	富士電機	HV HS PSW/PA/PD/SW-Reg	400	300	100		600	1000	400	200	5	100	2	2.5	100	1	
ET-190	富士電機	HV HS PSW/PA/PD/SW-Reg	600	600	8		80	1000	600	200	5	5	1.2	1.8	5	0.1	
ET-191	富士電機	HV HS PSW/PA/PD/SW-Reg	600	600	12		100	1000	600	100	5	12	2	2.2	12	0.24	
ET-212	富士電機	HV HS PSW/PA/PD/SW-Reg	1000	1000	30		300	1000	1000	100	5	30	3	3.7	30	0.6	
ET-215	富士電機	SW-Reg/Motor/PA	1000	1000	100		960	1000	1000	40	5	60	2.8	3.5	60	2	
ET-227	富士電機	SW-Reg/Motor/PA	1000	1000	100		960	1000	1000	4	5	60	1	2	60	30	
ET-326	富士電機	HV HS PSW/PA/PD/SW-Reg	400	300	100		600	1000	400	200	5	100	2	2.5	100	1	
ET-365	富士電機	SW-Reg/PA	450	450	8		40	100	300	500	2	4	1.5	2	4	0.015	
ET-366	富士電機	SW-Reg/PA	60	60	7		40	100	60	4000	3	3	1.5	2.5	3	0.006	
ET-370	富士電機	HS SW/SW-Reg/PA	100	100	15		100	100	100	1	3	8	3	3.5	15	0.15	
ET-375	富士電機	HV HS PSW/PA/PD/SW-Reg	650		15		80	1000	600	100	5	15	2	2.5	15	0.5	
ET-378	富士電機	SW-Reg/PA	100	100	10		80	100	100	1	2	6	3	3.5	10	0.1	
ET-382	富士電機	Reg/PA	200	180	5		40	1000	200	700	4	1	1.5	2	1.5	0.05	
ET-385	富士電機	HV HS PSW/PA/PD/SW-Reg	400	400	6		40	100	400	400	1.5	4	1.5	2	4	0.01	

電 気 的 特 性 (Ta=25°C) [*印はtyp値]										コンプリ メンタリ	外 形	電 極 接 続 備 考	型 名	
fr (MHz)	V _{CE} (V)	I _C /I _E (A)	ton (μs)	SW Time tf (μs)	tstg (μs)	Cob (max) (pF)	Cre (max) (pF)	そ の 他 の 主 要 項 目						
								項 目	特 性					測 定 条 件
200*	10	-0.05						R1/R2	1K/1K		DTB113E*	6種類	R	DTD113E*
200*	10	-0.05						R1/R2	1K/10K		DTB113Z*	6種類	R	DTD113Z*
200*	10	-0.05						R1/R2	10K/10K		DTB114E*	6種類	R	DTD114E*
200*	10	-0.05						R1	10K		DTB114T	6種類	R	DTD114T*
200*	10	-0.05						R1/R2	2.2K/2.2K		DTB123E*	6種類	R	DTD123E*
200*	10	-0.05						R1	2.2K		DTB123T	6種類	R	DTD123T*
200*	10	-0.05						R1/R2	2.2K/10K		DTB123Y*	6種類	R	DTD123Y*
200*	10	-0.05						R1/R2	3.3K/10K		DTB133H*	6種類	R	DTD133H*
200*	10	-0.05						R1/R2	4.7K/4.7K		DTB143E*	6種類	R	DTD143E*
200*	10	-0.05						R1	4.7K		DTB143T	6種類	R	DTD143T*
200*	10	-0.05						R1	6.8K		DTB163T	6種類	R	DTD163T*
			1.5	1	4							TO-3形	BCE	ET189
			1	1	3.5							SC-65	BCE	ET206
			1	0.8	4							SC-65	BCE	ET383
			1	0.8	4							(TO-3PF)	BCE	ET394
			0.5	0.15	1.5							(TO-3PF)	BCE	ET400
			0.5	0.15	1.5							(TO-3PF)	BCE	ET401
			1	1	3							(TO-3PF)	BCE	ET403
			1	1	2							(TO-3PF)	BCE	ET405
			4	4	12							(BBT-1)	EBC, Da/R	ET-102
			2	2.5	10							(TC-19類似)	-	ET-125
			4	3	10							(BBT-1)	EBC, Da/R	ET-127
			2	3	12							(BBT-11)	EBC, Da/R	ET-188
			1.5	1.5	15							SC-65	BCE	ET-190
			1.5	2	10							SC-65	BCE	ET-191
			3	2	12							(TC-19類似)	BCE, Da/R(保)	ET-212
												(BBT-11)	EBC, Da	ET-215
												(BBT-11)	EBC, R	ET-227
			2	3	12							(BBT-11)	EBC, Da/R	ET-326
												SC-67	BCE, Da/R	ET-365
												SC-67	BCE, Da/R	ET-366
			2	3	5							SC-65	BCE, Da/R	ET-370
			1	2	12							SC-65	BCE, Da/R	ET-375
												SC-65	BCE, Da/R	ET-378
												SC-67	BCE, Da	ET-382
			1	6	12							SC-67	BCE, Da/R	ET-385